

Ozone  
generator

Elektravägen 53  
SE-126 30 Hägersten, Sweden  
+46 10 252 30 00  
www.ozonetech.com

# ACT-3000

ACT-3000 is built with a stainless steel chassi with all controls easily accessible on the unit's side. The ozone generator has built-in monitoring of all vital parameters and shuts down the unit in case of any errors. The unit can also be controlled manually 0-100% using the power knob, or via the built-in digital input or the built-in 4-20 mA input.

ACT-3000 is used for confined spaces with odor problems or sanitation needs, such as garbage rooms, fire sanitation or sanitation of other enclosed spaces.

Option (not included): lockable wall-mount bracket.



## Technical specification

<b>Ozone production</b>	0 – 350 mg/h
Production	
<b>Feed gas (air)</b>	
Quality	Technically clean air (21% O <sub>2</sub> )
Filter class	F-7
Fan capacity, max	47 m <sup>3</sup> /h
<b>Ambient conditions</b>	
Temperature	0 to +40 °C (+32 to +104 °F)
Humidity, max	85 % (R. H.) Non-condensing
<b>Power supply</b>	
Voltage rating	230 VAC, 50 Hz
- Optional	115 VAC, 60 Hz
Power consumption, max	18 W



© Ozonetech

**ozonetech.**  
a MELLIFIQ brand

# Ozone generator

## Technical specification

### Dimensions

Size (H x W x D)	225 x 101 x 80 mm (8.9 x 4 x 3.1 in)
Weight	2 kg (4.4 lbs)
<b>IP class</b>	20
<b>Option (not included)</b>	Stainless steel lockable wall-mount bracket

## Advantages

- Stainless steel chassis
- Very low noise level
- Adjustable ozone production (0-100%)
- Compact design
- Easy to maintain
- Built-in digital input and output
- Built-in 4-20 mA interface

Elektravägen 53  
SE-126 30 Hägersten, Sweden  
+46 10 252 30 00  
[www.ozonotech.com](http://www.ozonotech.com)



© Ozonotech

**ozonotech.**  
a MELLIFIQ brand