



Elektravägen 53  
 SE-126 30 Hägersten, Sweden  
 +46 10 252 30 00  
 www.mellifiq.com

## Saniray Zeeron UVLX – 800 WATT AMALGAM SYSTEMS

UV System	Saniray Zeeron UVLX 3800-10	Saniray Zeeron UVLX 6800-14	Saniray Zeeron UVLX 16800-20	Saniray Zeeron UVLX 30800-30
Performance				
3rd party validation	USEPA UVDGM (2006)			
Certification	CE Marked			
<b>UV Lamps and Monitoring</b>				
Lamp power	800 W	800 W	800 W	800 W
Lamp number	3	6	16	30
Lamp life	16,000 hours			
Lamp design	TWISTLOK™ PLUS Connector - Quick release, Enhanced safety - 800 Watt high output Amalgam low pressure			
Validated UV monitoring	Validated UV monitor - AT-900 (calibrated) - IP66			
Variable power	100% power to 30% power (variable automatic dose pacing)			
<b>UV Chamber</b>				
Connection size (mm/ inch)	DN200/8"	DN250/10"	DN400/16"	DN600/24"
Connection type	BS4504 PN10 RF Flange			
Design pressure	7 Barg Design (10.5 Barg test)			
Material construction	316L Stainless Steel			
Internal / external-finish	0.8 µm Ra internal / Bead blasted			
Lamp and wiper access	Single ended access			
Quartz type	High purity quartz thimble			
Mounting	Legs			
Wiper system	Automatic wiper system			
Temperature probe	AT-487 (PT-100) - IP66			
Vent & drain ports	Yes			
Access hatch	Yes			
Ingress protection	IP66			
Installation	Horizontal			
Chamber options	Electropolish upgrade / super duplex 25% chrome steel / connection types			



© Saniray

**SANIRAY**  
 a MELLIFIQ brand



Elektravägen 53  
 SE-126 30 Hägersten, Sweden  
 +46 10 252 30 00  
 www.mellifiq.com

<b>Spectra II / Spectra II touch - local control cabinet</b>				
Design	Epoxy coated mild steel - IP54 standard			
Control type	Microprocessor			
Interface	Soft touch push button with 4 line text display / 7" touch screen HMI		7" touch screen HMI - full colour display	
Communication options	Ethernet / modbus RTU / Data Stream (other fieldbus options available)			
Lamp power supply	800 Watt electronic ballast			
Power consumption	2,649 W	5,280 W	14,080 W	26,400 W
Mains power	230 V (other voltages available)		400 V (other voltages available)	
Power requirements	1 phase + neutral + earth		3 phase + neutral + earth	
Frequency	50 Hz (60 Hz Optional)			
Protection	Door locked isolator, MCB protection			
Operating temperature	Max working ambient +45 °			
Operational information	Spectra II		Spectra II touch	

UV System	Saniray Zeeron UVLX 3800-10	Saniray Zeeron UVLX 6800-14	Saniray Zeeron UVLX 16800-20	Saniray Zeeron UVLX 30800-30
<b>Chamber Dimensions</b>				
A	2587 mm	2796 mm	3079 mm	3092 mm
B	479 mm	586 mm	666 mm	806 mm
C	2108 mm	2210 mm	2413 mm	2286 mm
D	1760 mm	1640 mm	1640 mm	1640 mm
E	N/A	N/A	N/A	N/A
F	381 mm	483 mm	635 mm	889 mm
G	275 mm	350 mm	379 mm	506 mm
H	250 mm	350 mm	700 mm	900 mm
I	300 mm	400 mm	800 mm	1000 mm
J	1750 mm	1725 mm	Adjustable	
K	479 mm	475 mm	479 mm	493 mm
Dry weight	175 kg	335 kg	460 kg	1145 kg
Wet weight	285 kg	640 kg	1110 kg	2330 kg

Panel dimensions	Saniray Zeeron UVLX 3800-10		Saniray Zeeron UVLX 6800-14	
Width	740 mm	940 mm	1400 mm	2000 mm
Height	1000 mm	1400 mm	2000 mm	2000 mm
Depth	340 mm	340 mm	600 mm	600 mm
Weight	85 kg	195 kg	680 kg	950 kg
Standard cable length	5 m			
Maximum cable length	35 m	35 m	35 m	35 m

## KEY FOOTPRINT DIMENSIONS

