

NPEC-7

PELLETISED COAL BASED ACTIVATED CARBON

NPEC-7 is a high activity Pelletised Activated Carbon manufactured by high temperature steam activation from selected grades of anthracite coal.

NPEC-7 is suitable for use in a wide variety of air purification and vapour phase applications such as odour & VOC control, tank vent emissions, solvent degreasing, compressed gas oil separation and HVAC systems.

The large number of transport pores, high surface area and exceptional pore volume of adsorption and transport pore structure enable NPEC-7 to provide rapid adsorption kinetics and high loading capacity.

SPECIFICATION

CTC Activity	min	70	%
Butane Activity	min	27	%
Moisture (as packed)	max	5	%
Ash Content	max	12	%

TYPICAL PROPERTIES

Hardness	97	%
Surface Area (BET N ₂)	1150	m ² /g
Apparent Density	0.45	g/cm ³
Adsorber Fill Density	400	kg/m ³

AVAILABLE SIZES

- 2mm (extruded pellet)
- 3mm (extruded pellet)
- 4mm (extruded pellet)
- 5mm (extruded pellet)

ADVANTAGES

- Optimised pore structure
- Very high adsorption capacity
- Large Internal surface area
- Excellent hardness
- Low dust
- High density
- Low pressure drop

STANDARD PACKAGING

- 25 kg sacks
- 500 kg big bags
- 550 kg big bags
- Bulk tankers



NOTICE:

This information is offered solely for your consideration and verification. It has been gathered from reference materials and/or test procedures and is believed to be true and accurate. None of this information shall constitute a warranty or representation, expressed or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes.

Elektravägen 53
SE-126 30 Hägersten, Sweden
+46 10 252 30 00
www.mellifiq.com



© Nodora



Nodora
a MELLIFIQ brand